

EO 2242 LED



Colour(s)



Ø195 mm



ORIENTABLE AND ADJUSTABLE ■ LED

- Circular recessed orientable spotlight for LED SPOT module, maximum 7 487 lumens
- CRI of 80 or 90
- MacAdam Ellipse: 3 SDCM
- Available in 3 000 K and 4 000 K
- 50 000 hours lamp life (L80B10)
- Luminous efficiency of system up to 136 lm/W
- Springs in pressure for easier installation
- Ring made of die-cast aluminium
- Static heat sink
- **Weight:** Approx. 1,7 kg
- **Driver(s):** Fixed, Dimmable driver DALI (CDIMMDALI)
- **Option(s):** Fast connector (CORD), Colour filters (FIL)

Driver(s)




Standards

Class I | IP 20 | 650°


Efficiency energy class



Beam(s)



Dimensions



ITEM	POWER	CONSUMPTION	LUMINOUS FLUX	SYSTEM EFFICIENCY	COLOUR TEMPERATURE	CRI	BEAM
EO 2242 LED 3000-930	23,5W	27,5W	3123 lumens	113,5 lm/W	3000 K	90	A
EO 2242 LED 3000-940	21,5W	25,5W	3131 lumens	123 lm/W	4000 K	90	A
EO 2242 LED 3500-830	24,6W	28W	3600 lumens	128,5 lm/W	3000 K	80	B
EO 2242 LED 3500-840	24,6W	28W	3696 lumens	132 lm/W	4000 K	80	B
EO 2242 LED 4000-830	28,6W	32,5W	4054 lumens	124,5 lm/W	3000 K	80	B
EO 2242 LED 4000-840	28,6W	32,5W	4160 lumens	128 lm/W	4000 K	80	B
EO 2242 LED 4000-930	30,5W	34W	3974 lumens	117 lm/W	3000 K	90	A
EO 2242 LED 4000-940	30,5W	34W	4246 lumens	125 lm/W	4000 K	90	A
EO 2242 LED 5000-830	38,7W	43W	5129 lumens	119 lm/W	3000 K	80	B
EO 2242 LED 5000-840	38,7W	43W	5262 lumens	122,5 lm/W	4000 K	80	B
EO 2242 LED 7000-830	49,2W	55W	7298 lumens	132,5 lm/W	3000 K	80	A
EO 2242 LED 7000-840	49,2W	55W	7487 lumens	136 lm/W	4000 K	80	A